

Configuratie standard

- disponibile in variante: PS125™ (fara imprimanta) sau PS125 OneStep™ (cu imprimanta).
- cote reduse de gabarit (56 x 48 cm).
- suport rotativ ce asigura alimentarea ergonomica si rapida cu pungi Autobag pre-deschise la rola.
- display-uri reglare/ control prietenoase si luminoase, usor lizibile si un meniu de navigare simplu
- stocheaza pana la 10 job-uri diferite de ambalare ce pot fi accesate/ rulate oricand ulterior
- sigileaza automat pungi si contorizarea pachetelor rezultate. Comanda de sigilare automata Push-to Seal™ sau actionarea de la pedala de picior
- dispozitiv Auto Thread™ pentru o facila schimbare a rolor de pungi

- suport reglabil de fixare a rolei cu pungi
- ghidajul pungilor asigura pozitionarea exacta a pungii in vederea imprimarii, alimentarii si lipirii
- conexiuni ptr. extindere comunicare la imprimanta: USB serial, parale si ethernet
- cap de imprimanta rabatabil pentru o mai buna curatare/ mentenanta

Optiuni

- aerator pungi
- palnii de alimentare
- software ptr. etichetare AutoLabel™
- chit de baza – piese de schimb

Dotari mecanice



Imprimanta ce asigura o buna calitate a imprimarii. Rabatabila deci usor de intretinut/ manevrat la schimbarea consumabilelor (banda termotransfer).



Baza masini echipata cu suport rotativ ce asigura acces usor la rola de pungi. Dispozitivul AutoThread™ usureaza manevrarea la schimbarea rolor.



Zona de incarcare deschisa si bara mobile de sigilare imbunatatesc flexibilitatea in alimentare si cresc siguranta in utilizare

Parametrii tehnici:

	PS 125	PS 125 OneStep
Greutate:	37 kg	50 kg
Partea electrica:	110/220 V CA, 50/60 Hz: 4.0 A	110/220 V CA, 50/60 Hz: 4.0 A
Zona incarcare:	pana la 86 mm	pana la 86 mm
Grosime pungi:	35 - 100 my	35 - 100 my
Marime pungi:	lat.: 50 - 250 mm lungime 100 - 430 mm	lat.: 50 - 250 mm lungime 100 - 430 mm
Greutate max. bun de ambalat:	1.1 kg	1.1 kg



Configurari posibile

Imprimanta ce asigura o buna calitate a imprimarii. Rabatabila deci usor de intretinut/ manevrat la schimbarea consumabilelor (benzii termotransfer).